


Heavy Duty Bolted

GLX Rigid Bolted Heavy Duty Trench Shield

- ★ **Constructed of high strength steel and high alloy steel**
- ★ **Wall thickness available in 6", 8" or 10"**
- ★ **Vertical front knife edges**
- ★ **Professional Engineer Certified**
- ★ **Extra long bottom knife**
- ★ **3/4" front and bottom anti-wear edges**
- ★ **Lift, push, or pull by direct bucket contact**
- ★ **Guides for rear cut off plate**
- ★ **Interchangeable widths**
- ★ **Choice of heights: 4', 6', 8', 10' or 12' high panels**
- ★ **Standard lengths to 40'**
- ★ **Impact distribution pads**
- ★ **Hardwood core**



GLX CLASS BOLTED BOX

6" WALL-6GLX TRENCH SHIELD MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A 25	B 45	C 60	80
6GLX417	4'	17'	5050#	84	48	37	29
6GLX419	4'	19'	5500#	56	33	26	20
6GLX421	4'	21'	6000#	52	31	24	19
6GLX425	4'	25'	7050#	43	26	20	16
6GLX427	4'	27'	7500#	35	21	17	14
6GLX617	6'	17'	7200#	84	48	37	29
6GLX619	6'	19'	7900#	56	33	26	20
6GLX621	6'	21'	8600#	52	31	24	19
6GLX625	6'	25'	10000#	43	26	20	16
6GLX627	6'	27'	10500#	35	21	17	14
6GLX817	8'	17'	8600#	72	42	32	25
6GLX819	8'	19'	9300#	56	33	26	20
6GLX821	8'	21'	10000#	52	31	24	19
6GLX825	8'	25'	12000#	43	26	20	16
6GLX827	8'	27'	12500#	35	21	17	14
6GLX1017	10'	17'	9800#	75	43	34	26
6GLX1019	10'	19'	11500#	62	36	28	22
6GLX1021	10'	21'	12000#	50	30	23	18



16' HIGH HEAVY DUTY BOLTED TRENCH BOX



BOX CULVERT INSTALLATION WITH 18' HIGH X 18' WIDE CLEARANCES



HEAVY DUTY BOLTED SPREADERS FEATURE "WINDOWS" FOR BETTER OPERATOR VIEWING. ADDITIONAL SPACERS CAN BE ADDED FOR WIDTH CHANGES



THE 8GLX1025 UNIT SHOWN
HERE IS 10' HIGH X 25' LONG



12 FT. HIGH AND 30 FT. LONG

8" WALL-8GLX TRENCH SHIELD

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A	B	C	
8GLX417	4'	17'	5400#	88	51	39	30
8GLX419	4'	19'	5950#	72	42	32	25
8GLX421	4'	21'	6500#	68	40	31	24
8GLX425	4'	25'	7500#	52	31	24	19
8GLX427	4'	27'	8200#	43	26	20	16
8GLX617	6'	17'	7500#	112	64	49	38
8GLX619	6'	19'	8000#	90	52	40	31
8GLX621	6'	21'	8800#	72	42	32	25
8GLX625	6'	25'	10200#	52	31	24	19
8GLX627	6'	27'	10700#	44	26	21	17
8GLX817	8'	17'	9350#	79	46	35	27
8GLX819	8'	19'	10300#	64	37	29	23
8GLX821	8'	21'	11250#	56	33	26	20
8GLX825	8'	25'	13000#	48	28	22	18
8GLX827	8'	27'	14000#	43	26	20	16
8GLX1017	10'	17'	11500#	106	61	47	36
8GLX1019	10'	19'	12700#	88	51	39	30
8GLX1021	10'	21'	13900#	80	46	36	28
8GLX1025	10'	25'	16250#	48	28	22	18
8GLX1027	10'	27'	17500#	43	26	20	16



"BOX IN A BOX"
METHOD OF CONTAINMENT
CONTACT FACTORY
FOR DETAILS

HEAVY DUTY BOLTED BEAM STYLE

MODEL	WIDTH	WEIGHT
GLX24	24"	750
GLX30	30"	800
GLX36	36"F & 32"R	850
GLX42	42"F & 38"R	950
GLX48	48"F & 44"R	1050
GLX54	54"F & 50"R	1175
GLX60	60"F & 56"R	1300
GLX72	72"F & 68"R	1500
GLX84	84"F & 80"R	1900
GLX96	96"F & 92"R	2600
GLX108	108"F & 104"R	2800
GLX120	120"F & 116"R	3200



TAPERED FRONT TO REAR. FACILITATES
DRAGGING FORWARD



THE 10GLX1225 UNIT SHOWN
HERE IS 12' HIGH X 25' LONG AND
MADE OF HIGH ALLOY STEEL

10" WALL-10GLX TRENCH SHIELD

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A	B	C	
10GLX621	6'	21'	11000#	88	51	39	30
10GLX625	6'	25'	12850#	60	35	27	22
10GLX627	6'	27'	13900#	48	28	22	18
10GLX629	6'	29'	14900#	43	26	20	16
10GLX631	6'	31'	15900#	36	22	17	14
10GLX821	8'	21'	14000#	88	51	39	30
10GLX825	8'	25'	16500#	60	35	27	22
10GLX827	8'	27'	17200#	48	28	22	18
10GLX829	8'	29'	18800#	44	26	21	17
10GLX831	8'	31'	20000#	40	24	19	15
10GLX835	8'	35'	22600#	31	19	15	12
10GLX1021	10'	21'	17200#	96	55	42	33
10GLX1025	10'	25'	20000#	68	40	31	24
10GLX1027	10'	27'	21500#	58	34	27	21
10GLX1029	10'	29'	22950#	50	30	23	18
10GLX1031	10'	31'	24400#	46	27	22	17
10GLX1035	10'	35'	27600#	37	22	18	14

**EXTRA HEAVY DUTY BOLTED
DRUM STYLE**

MODEL	WIDTH	WEIGHT
XGLX48	48"F & 44"R	1575
XGLX54	54"F & 50"R	1775
XGLX60	60"F & 56"R	2850
XGLX66	66"F & 62"R	3125
XGLX72	72"F & 68"R	3425
XGLX84	84"F & 80"R	4000
XGLX96	96"F & 92"R	4575
XGLX108	108"F & 104"R	5150
XGLX120	120"F & 116"R	5725
XGLX132	132"F & 128"R	6200
XGLX144	144"F & 140"R	6600
XGLX168	168"F & 164"R	7700
XGLX192	192"F & 188"R	8800

**AMERICAN
SHORING INC.**

1.800.407.4674
www.americanshoring.com