

Medium Duty Trench Shields



**Same as the "SSW"
Light Steel except with
a full interior plate**

- ★ Professional engineer certified
- ★ High strength steel construction
- ★ 4" wall thickness standard
- ★ 3" wall thickness available
- ★ Utilizes pinned in place pipe spreaders
- ★ Lifting lugs standard
- ★ Hardwood filled top & front rails
- ★ Reinforced bottom cutting edges and anti-wear bar standard
- ★ Stackable
- ★ Factory painted
- ★ Optional Styrofoam filled
- ★ Medium & Heavy Duty Series available

4" LIGHT WEIGHT STEEL SINGLE SIDE WALLS

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A 25	B 45	C 60	C 80
4SSW46L	4'	6'	1525#	93	53	41	32
4SSW48L	4'	8'	1800#	89	51	39	31
4SSW410L	4'	10'	2150#	64	37	29	23
4SSW412L	4'	12'	2450#	45	27	21	17
4SSW416L	4'	16'	3050#	31	19	15	12
4SSW66L	6'	6'	2075#	93	53	41	32
4SSW68L	6'	8'	2450#	89	51	39	31
4SSW610L	6'	10'	2900#	57	33	26	21
4SSW612L	6'	12'	3475#	47	28	22	18
4SSW616L	6'	16'	4550#	31	19	15	12
4SSW86L	8'	6'	2550#	93	53	41	32
4SSW88L	8'	8'	2950#	64	37	29	23
4SSW810L	8'	10'	3550#	50	30	23	18
4SSW812L	8'	12'	4150#	38	23	18	15
4SSW816L	8'	16'	5400#	31	19	15	12
4SSW820L	8'	20'	6550#	24	15	12	10

4" LIGHT WEIGHT STEEL DOUBLE SIDE WALLS

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A 25	B 45	C 60	C 80
4SDW412L	4'	12'	2760#	69	39	30	23
4SDW414L	4'	14'	3071#	49	28	22	17
4SDW416L	4'	16'	3383#	37	22	17	13
4SDW612L	6'	12'	3614#	64	37	29	22
4SDW614L	6'	14'	4057#	50	29	23	18
4SDW616L	6'	16'	4500#	38	23	18	14
4SDW812L	8'	12'	4469#	63	37	29	23
4SDW814L	8'	14'	5042#	51	30	24	19
4SDW816L	8'	16'	5616#	39	24	19	15

Other sizes available on request