



36' LONG HEAVY DUTY TRENCH BOX WITH AVENGER STYLE END CLOSURE PLATES



SUPER Double Wall

SHOWN WITH FIVE (5) PIPE SPREADER SYSTEM



SUPER Double Wall

SHOWN WITH FOUR (4) PIPE SPREADER SYSTEM. "H" STYLE BRACKETS PERMIT STACKING AND LOCKING OF BOXES TOGETHER. STACKING TUBES ALSO AVAILABLE.

6" HEAVY DUTY DOUBLE WALL

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A	B	C	C
				25	45	60	80
6SDW416H	4'	16'	5255#	99	70	53	41
6SDW420H	4'	20'	6319#	77	44	33	25
6SDW424H	4'	24'	7383#	53	31	23	18
6SDW616H	6'	16'	7133#	102	71	54	42
6SDW620H	6'	20'	8650#	79	45	34	26
6SDW624H	6'	24'	10168#	54	31	24	19
6SDW626H	6'	26'	10927#	46	27	21	16
6SDW628H	6'	28'	11634#	40	23	18	14
6SDW816H	8'	16'	9009#	93	54	41	32
6SDW820H	8'	20'	10981#	76	44	34	26
6SDW824H	8'	24'	12952#	55	32	25	20
6SDW826H	8'	26'	13938#	47	28	22	17
6SDW828H	8'	28'	14852#	41	24	19	15
6SDW1016H	10'	16'	10886#	86	50	39	30
6SDW1020H	10'	20'	13311#	70	41	32	25
6SDW1024H	10'	24'	15737#	55	33	26	21
6SDW1026H	10'	26'	16950#	48	29	23	18
6SDW1028H	10'	28'	18070#	41	25	20	16

8" HEAVY DUTY DOUBLE WALL

MODEL	HEIGHT	LENGTH	WEIGHT	APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE			
				A	B	C	C
				25	45	60	80
8SDW416H	4'	16'	5830#	99	93	70	53
8SDW420H	4'	20'	6982#	99	58	44	34
8SDW424H	4'	24'	8132#	71	40	31	23
8SDW616H	6'	16'	7812#	99	96	73	55
8SDW620H	6'	20'	9437#	99	60	46	35
8SDW624H	6'	24'	11062#	74	43	32	25
8SDW626H	6'	26'	11874#	62	36	28	21
8SDW628H	6'	28'	12638#	54	31	24	19
8SDW816H	8'	16'	9794#	99	57	44	34
8SDW820H	8'	20'	11892#	80	46	36	28
8SDW824H	8'	24'	13990#	68	39	31	24
8SDW826H	8'	26'	15040#	63	37	28	22
8SDW828H	8'	28'	16022#	55	33	26	21
8SDW1016H	10'	16'	11775#	102	59	46	36
8SDW1020H	10'	20'	14348#	81	47	37	29
8SDW1024H	10'	24'	16920#	68	40	31	25
8SDW1026H	10'	26'	18206#	63	37	29	23
8SDW1028H	10'	28'	19404#	55	33	26	21

4-PIPE SPREADER SYSTEM

STANDARD CONFIGURATION FOR 4', 6' & 8' HIGH UNITS (TAPER OPTIONAL)

HPS HEAVY PIPE SPREADERS

For deep cut sidewalls (taper optional) (4) 8" schedule 80 pipes

MODEL	WIDTH	WEIGHT
HPS-4-24	24"	500#
HPS-4-30	30"	600#
HPS-4-36	36"	700#
HPS-4-42	42"	775#
HPS-4-48	48"	850#
HPS-4-54	54"	950#
HPS-4-60	60"	1025#
HPS-4-72	72"	1200#
HPS-4-84	84"	1400#
HPS-4-96	96"	1550#
HPS-4-108	108"	1700#
HPS-4-120	120"	1900#

★ SETS INCLUDE PINS AND KEEPERS

5-PIPE SPREADER SYSTEM

STANDARD FOR 10' HIGH SIDEWALLS OPTIONAL FOR 8' HIGH SIDEWALLS (TAPER OPTIONAL)

5 PIPE SPREADER SYSTEM

Standard for 10' high sidewalls optional for 8' high sidewalls (taper optional) (5) 8" schedule 80 pipes

MODEL	WIDTH	WEIGHT
HPS-5-24	24"	465#
HPS-5-30	30"	572#
HPS-5-36	36"	680#
HPS-5-42	42"	790#
HPS-5-48	48"	900#
HPS-5-54	54"	1005#
HPS-5-60	60"	1115#
HPS-5-72	72"	1480#
HPS-5-84	84"	1670#
HPS-5-96	96"	1920#
HPS-5-108	108"	2130#
HPS-5-120	120"	2350#

*** PSF Ratings and depths are based on short term exposure with excavation open a period of time equal to 24 hours or less. Consult manufacturer should long term exposure be required. Depths are based on A, B, C soil types as described in OSHA's 29 CFR Part 1926 Subpart P, October 31, 1989 with Type A not exceeding 25 PSF per foot of depth. Type B not exceeding 45 PSF per foot of depth. Type C-60 not exceeding 60 PSF per foot of depth and Type C-80 not exceeding 80 PSF per foot of depth. Determine actual soil pressures and consult Manufacturers Tabulated Data prior to each use.



1.800.407.4674
www.americanshoring.com